



Part Number: 35616

Hook-Up/Lead Wire UL AWM Style 3173 - XL-DUR®, (1) 16 AWG (26x30)
TC, XLPE, 600V, 125°C

[Request Sample](#)

Product Description

One 16 AWG stranded (26x30) tinned copper conductor, cross-linked polyethylene insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor			
AWG	Stranding	Material	No. of Conductors
16	26x30	TC - Tinned Copper	1
Conductor Count:			1
Conductor Size:			16 AWG

Insulation			
Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
XLPE - Cross Linked Polyethylene	0.122 in	0.0315 in	0.03 in

Outer Jacket Material

Material
No Jacket

Electrical Characteristics

Conductor DCR	
Nominal Conductor DCR	
4 Ohm/1000ft	
Shielding:	Unshielded

Current	
Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	28 amps

Voltage	
UL Voltage Rating	
600 V	

Temperature Range

UL Temp Rating:	125°C
-----------------	-------

Mechanical Characteristics

Bulk Cable Weight:	14 lbs/1000ft
--------------------	---------------

Standards

UL AWM Style:	3173
CSA Rating:	600 V, 125°C
CSA Type:	CL1251
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-07-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	600 V RMS
--------------------	-----------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
35616 010500	Black	F
35616 0105000	Black	C I U Z
35616 0065000	Blue, Light	C I U Z
35616 0015000	Brown	C I U Z
35616 005500	Green, Dark	F
35616 0055000	Green, Dark	C I U Z
35616 0035000	Orange	C I U Z
35616 002500	Red	F
35616 0025000	Red	C I U Z
35616 009500	White	F
35616 0045000	Yellow	C I U Z

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'.
Footnote:	U - TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10,000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE)
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.
Footnote:	F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.